LT9211 --- Product Brief

MIPI/TTL/2-Port LVDS to MIPI/TTL/2-Port LVDS Converter

Features

MIPI Transmitter

Compliant with DCS1.02, D-PHY1.2 ,DSI1.2 and CSI-2 1.00
1 Clock Lane and 1~4 Configurable Data Lanes
Two Port Simultaneous Display Supported
Up to 1.8Gb/s per Data Lane
Resolution Up to 1920x1200 60Hz or any other Resolution whose Pixel Clk less than 200MHz
Data Lane and Polarity Swapping
Both Non-Burst and Burst Video Mode Supported
Support RGB666, Loosely RGB666, RGB888, RGB565, 16-bit YCbCr4:2:2, 24-bit YCbCr 4:2:2 Video Format

Dual-Port LVDS Transmitter

Compatible with VESA and JEIDA standard
1~2 Configurable Port
Two Port Simultaneous Display Supported
Resolution Up to 1920x1200 60Hz or any other Resolution whose Pixel Clk less than 200MHz
Support DE Mode
Data Port , Data Lane and Polarity Swapping
Programmable Pre-emphasis
Support output SSC(30KHz ± 5%)

TTL Output

Support 24-bit RGB and BT656/BT1120
Both DDR and SDR Sampling supported
Support both 1.8V and 3.3V Voltage Output
Resolution Up to 1920x1200 60Hz or any other Resolution whose Pixel Clk less than 200MHz

MIPI Receiver

Compliant with DCS1.02, D-PHY1.2 ,DSI1.2 and CSI-2 1.00
1 Clock Lane and 1~4 Configurable Data Lanes
Two Port Input switchable
Up to 1.8Gb/s per Data Lane
Resolution Up to 1920x1200 60Hz or any other Resolution whose Pixel Clk less than 200MHz
Data Lane and Polarity Swapping
Both Non-Burst and Burst Video Mode Supported
Support RGB666, Loosely RGB666, RGB888, RGB565, 16-bit YCbCr4:2:2, 24-bit YCbCr 4:2:2 Video Format

Dual-Port LVDS Receiver

Compatible with VESA and JEwia86.8( )dEƒ3oth Non-Bu1~E2 Confi Lo
Resolution whose Pixel Clk less than 200MHz

LONTIUM CONFIDENTIAL

LONTIUM CONFIDEN

